

| Description of the Product | |
|----------------------------|--------------------------------|
| Colors | Eggshell, Wicker, Pumice |
| Nominal Sizes | 12x24 |
| Body Composition | Glazed Porcelain |
| Finishes | Matte |
| Edges | Pressed |
| Thickness | 8mm (12x12), 9mm (12x24) |
| Intended Use | Residential & Light Commercial |

| Porcelain Technical Characteristics | Test Method | ANSI A137.1 | Series Average Values |
|--|-------------|-----------------------------------|---------------------------------------|
| Water Absorption | ASTM C373 | ≤ 0.5 % | Conforms |
| Breaking Strength | ASTM C648 | ≥ 250 lbf | ≥ 350 lbf |
| Linear Thermal Expansion | ASTM C372 | Not Required | Conforms |
| Thermal Shock Resistance | ASTM C484 | No sample must show visible signs | Conforms |
| Chemical Resistance | ASTM C650 | Not Required | As Reported |
| Stain Resistance | ASTM C1378 | Not Required | As Reported |
| Freeze/Thaw Resistance | ASTM C1026 | - | Conforms |
| Bond Strength | ASTM C482 | ≥ 50 PSI (0.34 MPa) | Conforms |
| Shade Variation | ANSI 137.1 | Manufacturer Statement | V2 Slight Variation |
| Thickness | ASTM C499 | Max Range 0.040" (1.02 mm) | max ± 0.030 inch |
| Surface Hardness | Mohs Scale | As Reported | 7 Mohs |
| Warpage Edge | ASTM C485 | - | Conforms |
| Warpage Diagonal | ASTM C485 | - | Conforms |
| Flame Spread | ATSM E84 | - | Class A |
| Dynamic Coefficient of Friction (DCOF) | A326.3 | A326.3 | Matte Interior, Wet Plus (IW+) |

Notes:

1. All or most items in this collection comply with these specifications. Color, texture, and finish variations may occur due to the nature of the product.
2. Country of origin and other product features and characteristics are subject to change due to manufacturing efficiencies and other factors.
3. See retailer or product packaging to verify country of origin and other product characteristics.
4. Safety Data Sheet available upon request.
5. Color availability may vary by format.
6. For General Tile Installation, Care and Maintenance, and Warranty information visit www.floridatile.com.