

Description of the Product	
Colors	Loom, Sand, Drift, Twill, Moss, Denim, Suede, Ashford, Harrington, Westbridge, Crosby, Bexley
Nominal Sizes	3.75x12, 12x24, 24x48
Body Composition	Color Body Porcelain
Finishes	Matte
Edges	Rectified
Thickness	9mm
Intended Use	Residential, Light Commercial, Heavy Commercial

Porcelain Technical Characteristics	Test Method	ANSI A137.1	Series Average Values
Water Absorption	ASTM C373	≤ 0.5 %	Conforms
Breaking Strength	ASTM C648	≥ 250 lbf	≥ 400 lbf
Linear Thermal Expansion	ASTM C372	Not Required	Conforms
Thermal Shock Resistance	ASTM C484	No sample must show visible signs	Conforms
Chemical Resistance	ASTM C650	Not Required	Conforms
Stain Resistance	ASTM C1378	Not Required	Conforms
Freeze/Thaw Resistance	ASTM C1026	-	Conforms
Bond Strength	ASTM C482	≥ 50 PSI (0.34 MPa)	Conforms
Shade Variation	ANSI 137.1	Manufacturer Statement	<b>V2 Slight Variation</b> Loom, Sand, Drift, Twill, Moss, Denim, Suede <b>V3 Moderate Variation</b> Ashford, Harrington, Westbridge, Crosby, Bexley
Thickness	ASTM C499	Max Range 0.040" (1.02 mm)	max ± 0.030 inch
Surface Hardness	Mohs Scale	As Reported	7 Mohs
Warpage Edge	ASTM C485	-	Conforms
Warpage Diagonal	ASTM C485	-	Conforms
Dynamic Coefficient of Friction (DCOF)	A326.3	A326.3	<b>Matte</b> Interior, Wet Plus (IW+)

**Notes:**

1. All or most items in this collection comply with these specifications. Color, texture, and finish variations may occur due to the nature of the product.
2. Country of origin and other product features and characteristics are subject to change due to manufacturing efficiencies and other factors.
3. See retailer or product packaging to verify country of origin and other product characteristics.
4. Safety Data Sheet available upon request.
5. Color availability may vary by format.
6. For General Tile Installation, Care and Maintenance, and Warranty information visit [www.floridatile.com](http://www.floridatile.com).

